

REVISIONES/REVISIONS				
INDICE ISSUE	DOC. APROBACION AUTHORITY DOC.	FECHA DATE	APROB APPD	VERIF SYST
		<i>XX-XX-XX</i>		



1. AISLE WIDTHS MUST MEET REQUIREMENTS SET FORTH IN EASA CS 25.815
2. EMERGENCY EXITS MUST BE ACCESSIBLE PER EASA CS 25.813
3. EMERGENCY EXIST MUST BE MARKED IN ACCORDANCE WITH EASA CS 25.811
4. ALL LIFE VESTS MUST CONFORM TO ETSO C-13
5. PASSAGEWAY TO ALL TYPE I AND TYPE III EXITS MUST NOT BE LESS THAN 20"
6. CREW OXYGEN MASKS MUST MEET ALL REQUIREMENTS IN EASA CS 25.1439
7. STORAGE PROVISIONS FOR ALL EMERGENCY EQUIPMENT MUST BE MARKED TO IDENTIFY THEIR CONTENTS IAW EASA CS 25.1561
8. "FASTEN SEAT BELT" AND "NO SMOKING" SIGNS MUST BE VISIBLE TO EACH PERSON SEATED IN THE PASSENGER CABIN
9. ALL SEAT BACKS AND BULKHEADS MUST HAVE "FASTEN SEAT BELT WHILE SEATED" PLACARD
10. SEAT REFERENCE LINE IS TAKEN FROM POINT OF ATTACHMENT TO AIRCRAFT SEAT TRACKS
11. LOPA FOR 233Y PAX SEATS ARRANGED IAW SERVICE BULLETIN A3015-SB001. REFER TO SHEET 2 OF THIS DRAWING FOR SEAT PART LIST AND CONFIGURATION

- THE ELEMENTS AFFECTED BY THIS MODIFICATION ARE:
- Y/C PASSENGER DOUBLE SEATS: SICMA AERO SEAT SERIES 9585 - CMM 25-00-89
 - Y/C PASSENGER DOUBLE AND TRIPLE SEATS: SICMA AERO SEAT SERIES 7124 - CMM 25-19-53
 - Y/C PASSENGER TRIPLE SEATS: SICMA AERO SERIES 8712:- APPLICABLE CMM
 - Y/C PASSENGER DOUBLE SEATS: SICMA AERO SERIES 7108:- CMM 25-20-80
12. A/C SEATS MUST COMPLY RESPECTIVELY TSO OR ETSO
13. TIGHTEN THE SEAT LEG TRACK FITTING FASTENER IAW VALUES OF APPLICABLE CMM
14. INSTALLATION TOLERANCES: LINEAR ± 1 mm, ANGULAR $\pm 0.5^\circ$
15. (SEE POST-INSTALLATION NOTES IN THIS SHEET)

1. ENSURE EACH OXYGEN MASK DROPS WITHIN THE REQUIRED ZONE ABOVE PASSENGER SEAT
2. ENSURE NO SMOKING/FASTEN SEAT BELT SIGN IS VISIBLE TO EACH PASSENGER WHILE SEATED
3. ENSURE EMERGENCY ESCAPE PATH MARKING IS DIRECTLY VISIBLE ALONG THE WHOLE PASSENGER CABIN AND ALSO NO OBJECT OR CARPET COVERS IT AT ANY POINT OF EMERGENCY EXIT AISLES

PART LIST IN THIS SHEET															
CAD	CATIA	ESTE DOCUMENTO ES PROPIEDAD DE S4A TODOS LOS DERECHOS RESERVADOS		THIS DOCUMENT IS PROPERTY OF S4A WHICH RESERVES ALL RIGHTS		PROTECCION SUPERFICIAL PROTECTIVE FINISH									
		RUGOSIDAD DE LA SUPERFICIE Ra SURFACE ROUGHNESS Ra		TOLERANCIAS NO ESPECIFICADAS LIMITS NOT STATED		SEGUN ESPESOR DE CAPA LAYER THICKNESS									
		SEGUN PER ✓ / (✓ ✓ ✓) ¹ mm		SEGUN PER DIN7168 BASTA *		COLOR _____ LINE # _____ ¹ mm									
CLASE/CLASS	MARCA DE IDENTIF IDENT MARKINGS		N/A		PARTE INTERCAMBABLE INTERCHANGEABLE PART		SI/YES NO		PARTE IDENTIFICABLE IDENTIFIABLE PART		SI/YES NO				
PROYECCION SECTION		DBLUJ DWN		S4A		F. GUERRERO		RESIST STRESS		F. GUERRERO		FECHA DATE		JUL/18	
		APROB APPD		A. SANCHEZ		VERIF SYST		A. SANCHEZ		PESO WT		Kg			
ESCALA SCALE:	COLECC COLLEC	DESIGNACION: TITILE:				LOPA 233Y PAX A310-300		Nº NO		A3015-25200000					
X:X								HOJA SHEET		1/1		INDICE ISSUE		1	